

Model 4003-A C-Band LNB

Specifications

INPUT FREQUENCY TO EXTERNAL LNB	3.4 - 4.2 GHz
IF Output Frequency	950 to 1750 MHz, Inverted
Gain	55 db min, 70 db max
Level Stability	1 dB p-p Max, 27 MHz segment
1 Db compression point	+9 dBm min
Noise Temperature	20 K
Image Rejection	45 dB min
Local Oscillator Frequency	5.150 GHz
Local Oscillator Stability	±5 kHz
Local Oscillator Phase Noise	-75 dBc/Hz @ 1 kHz
Local Oscillator Leakage	-45 dBm max, measured at Waveguide input
Input Connector	CPR229G Waveguide
Output Connector	Type F, Female, 75 ohm
Dimensions	7.1" x 4.0" x 2.8"
Weight	25 oz
Operating Temperature	- 30 to +55 C
Relative Humidity	up to 100 % condensation and Frost
Power	+15 to 24 VDC, supplied on center conductor of IF cable
Current Draw	350 ma, typical

Other Frequency Ranges are available.

Please see <http://www.satsyscorp.com> for more information.



Satellite Systems Corporation
 101 Malibu Drive Virginia Beach, VA 23452 USA
 Voice (757) 463-3553 Fax (757) 463-3891
sales@satsyscorp.com